March 11th A D. 1858. han the following lines and Made the following borners in Letion 11. If g R 1. E. for Datid west Firam Meon William Swisher & others. ligth of the line E. the head throng the Center 324 poles 19. luks hugth north and louth 328, John 500' high of the line salt of center longthe west 20 161. Poles 2000 163. 11 56 lugth South le lo lo Corner Made at Outer white ash 18 wiches diameter A23/ h, 26/ links dist Maple 12 inches diameter 8826 20 links dist. leoner made and witness Lice 80 poles 400. East of the center Sugar 10 inchis diam 865 4 24 links dett. B. oals 15 in diam A 22/2 6 45 lhs dett lingth of the line from the A & box to the A/2 mile post 163. poles 500, leorner made equidistant between Said borners poplar 20 in dian A 840 1 29 Chr dist red Oak 6 wiches dian A250 h, 15% lbs dist borner made at 88 Course of I'm greater or 1/4. White oak 36 inches diam A 32/2 1/2 23 3 hinters det woah 12. in diam & 87/2 4, 39%. Chrs di stant Di Stanes from Mo to R. 81. poles borner made at Mb the 8 h Corner of A 1/4. of A & ger withing B. Dahr 20 wehrs draw \$350 6 9 links dist Sugar 15 in diam A 820 h, 25 Chr dist lugth of the line from the A h. box of Sec 11, 163 poles Former made 81 poles 88, poles South of of The A The Corner witness her to oak. 18 inches diameter 850 h 16/2 lubes ditt bonner and witness where made at the louth East borne of Ahy of Ah guarto Roah 24 in dian Corner Made 81 poles & 38 poles west of the center Sugar 15 inches diam A4608 29- Mrs ditt Bek. ash I in diam &32 & 42/ lin his dist, Regimning at the Name time the following lot of land Vg B. I. Last then South 81 poles post of Destion no 11 24 inches diain & 170 80 3, Ches dist to Oak 168 6 44/2 this det then A850 81. polis 760 polis to a stone borner withof Les B. ash 4 in diane A 20/2 h 6 lbn dist B ash 4 in diam & 48 6 22. Chr dist, then South 81. por

so poly than 81. holes the nots to the Beginning

laune.

intablished the

Nan of N. Wan

I bentin of S.G. gr.

South Mist con of

num Establis

Malin Malin States

stablished at a

Wall not the

Allowing corner